

# LED HIGHBAY LIGHT

## NUVI 6000 Series



SPECIFICATIONS	DATA		
	MIN.V	TYP.V	MAX.V
PRODUCT CODE	See List		
INPUT VOLTAGE	185V	230V	265V
INPUT CURRENT	705mA	579mA	508mA
OUTPUT CURRENT	2.58A	2.58A	2.58A
POWER FACTOR	0.98	0.96	0.95
OUTPUT POWER (VA)	115W		
POWER (MEASURED)	128W	128W	127W
INPUT POWER (VA)	130W	133W	135W
EFFICIENCY	90%		
LIGHT SOURCE	LED		
COLOUR TEMPERATURE	See Product List		
EFFICACY	102 Lm/W		
CRI	>70		
LUMINOUS INTENSITY	UP TO 13000lm		
FEATURE	INSTANT ON SOFT START		
PROTECTION AVAILABLE	Over Temperature control, Emissions, ESD, Surge, Dips & interruptions.		
COMPLY TO SPECIFICATION	UL60950-1, IEC60950-1, EN60950-1, ANSI/AAMI		
OPERATING TEMPERATURE	-20°C	°C	+70°C
STORAGE TEMPERATURE	-40°C	°C	+85°C
DIMENSIONS (mm)	195(L)	195(B)	260(H)
WEIGHT	1.35Kg		

PART NUMBER	DESCRIPTION
NUVI.6001.230A.E40.133.3Ko	HIGHBAY - 230Vac 13000Lm 3000K - 60deg
NUVI.6001.230A.E40.143.4Ko	HIGHBAY - 230Vac 14000Lm 4000K - 60deg
NUVI.6001.230A.E40.143.5Ko	HIGHBAY - 230Vac 14000Lm 5000K - 60deg
NUVI.6002.230A.E40.133.3Ko	HIGHBAY - 230Vac 13000Lm 3000K - 90deg
NUVI.6002.230A.E40.143.4Ko	HIGHBAY - 230Vac 14000Lm 4000K - 90deg
NUVI.6002.230A.E40.143.5Ko	HIGHBAY - 230Vac 14000Lm 5000K - 90deg
NUVI.6003.230A.E40.133.3Ko	HIGHBAY - 230Vac 13000Lm 3000K - 120deg
NUVI.6003.230A.E40.143.4Ko	HIGHBAY - 230Vac 14000Lm 4000K - 120deg
NUVI.6003.230A.E40.143.5Ko	HIGHBAY - 230Vac 14000Lm 5000K - 120deg